S-18 Line *ANSI*

A perfect combination of high performance, quality and durability that meets the demands of the metalworking industry.



Backing	Polyester-satin fabric.
Mineral	Zirconia Alumina.
Grades	ANSI: 024 to 120 except 030.
Coating	Closed.
Ideal	METAL NONFERROUS METAL
Shapes	

Applications



CONTACT



PORTABLE









PNEUMATIC SANDER

ROLLS

WITH DISC SUCTION

OR VERTICAL SANDER

SANDER

SPECIALITIES

Applications

024 036 040

For polishing and intermediate finishing operations of stainless steel and high-hardness metals, such as stainless-steel canvases and glossy and woven materials.

EXTRA COARSE / COARSE / MEDIUM / FINE HEAVY POLISHING / INTERMEDIATE FINISHING

050 060 080 100

120

- Must be applied in the same direction to homogenize the scratches and care of the worked surface.
- Must be applied in the same direction to homogenize the scratches and care of the worked surface.
- For finishing processes on railings, pipes and stainless-steel attachments.
- Includes pretreatment for reflective polished finishes.

Characteristics

- Zirconia Alumina abrasive grains provide excellent performance and a good finish.
- Its structure with self-sharpening properties guarantee a medium to aggressive polishing action and excellent resistance to strong pressures.

